

## TXS-611SET - Wireless Microphone



**Multifrequency microphone system, with UHF PLL technology.**

- 1 hand-held microphone transmitter, 1 receiver, 1 plug-in PSU
- True diversity system
- 80 selectable UHF channels (863-865MHz)
- ACT function for transmitting the selected frequency to the hand-held microphone via infrared signal
- Automatic scan
- Volume and squelch controls
- Transmitting power can be switched at the hand-held microphone (high/low)
- Indication for channel, antenna A/B, ACT status and AF audio level (receiver), channel and battery status (hand-held microphone)
- Stable metal housing (receiver)

**Licence-free in the EU.**

## Technical data

Carrier frequency	: 863-865MHz
Transmitting power	: < 10mW (EIRP)
RF S/N ratio	: 105dB
Audio range	: 50-18,000Hz, ±3dB
Dynamic range	: 120dB
THD	: < 0.5%
Audio output	: 350mV/10k Ohm (jack) 25mV/10k Ohm (XLR, bal.)
Operating range	: approx. 30m
Admiss. ambient temp.	: 0-40 °C
Power supply	:
Transmitter	: 2 x 1.5V batt. AA size
Receiver	: via suppl. plug-in PSU
Dimensions	:
Transmitter	: Ø 52mm x 275mm
Receiver	: 152x38x120mm
Weight	:
Transmitter	: 235g
Receiver	: 482g
Connections	: 1 x 6.3mm jack, unbal. 1 x XLR, bal.

## TXS-631SET - Wireless Microphone



**Multifrequency microphone system, with UHF PLL technology.**

- 1 pocket transmitter, 1 tie clip microphone, 1 receiver, 1 plug-in PSU
- True diversity system
- 80 selectable UHF channels (863-865MHz)
- ACT function for transmitting the selected frequency to the pocket transmitter via infrared signal
- Automatic scan
- Volume and squelch controls
- Transmitting power and gain can be adjusted at the pocket transmitter
- Indication for channel, antenna A/B, ACT status and AF audio level (receiver), channel and battery status (pocket transmitter)
- Stable metal housing (receiver)

**Licence-free in the EU.**

## Technical data

Carrier frequency	: 863-865MHz
Transmitting power	: < 10mW (EIRP)
RF S/N ratio	: 105dB
Audio range	: 50-18,000Hz, ±3dB
Dynamic range	: 120dB
THD	: < 0.5%
Audio output	: 350mV/10k Ohm (jack) 25mV/10k Ohm (XLR, bal.)
Operating range	: approx. 30m
Admiss. ambient temp.	: 0-40 °C
Power supply	:
Transmitter	: 2 x 1.5V batt. AA size
Receiver	: via suppl. plug-in PSU
Dimensions	:
Transmitter	: 62x105x25mm
Receiver	: 152x38x120mm
Weight	:
Transmitter	: 88g
Receiver	: 482g
Connections	: 1 x 6.3mm jack, unbal. 1 x XLR, bal.